

Instructions for use Photomurals

(All motifs have been selected so that they can be cropped on all sides without any loss of overall effect).

Preparation of the surface

The wall should be prepared in the same way as if you were going to apply a Photomural: The substrate should be clean, smooth and grease-free - oil paints should be sanded off, wallpaper residue removed, roughness removed, holes and gaps filled. To ensure good drying, the substrate must be able to absorb moisture.

1. paste

Use the wallpaper paste supplied and use it in accordance with the instructions. Alternatively, commercially available wallpaper paste can also be used.

2. drawing the guide lines

As many walls are not exactly at right angles, we recommend starting from the centre of the wall. To do this, you need a horizontal and vertical guide line, which you draw on the centre of the wall using a spirit level and plumb line with a pencil.

3. pasting the sheets

Carefully paste sheet 4 with even strokes. Pay particular attention to the edges. Important: Allow the paste to swell on all sheets for 3 minutes and do not lay the pasted paper pieces on top of each other.



4/5. Attachment

Place the sheet on the guide lines and smooth it out from top to bottom and the air from the centre to the sides. Position sheets 6, 2, 8 and then sheets 3, 5, 1 and 7. Allow the sheets to overlap by 2-3 mm.

Drying

Drying must take place slowly to avoid gaping at the joint lines and cracking of the Photomural. Therefore, work at a room temperature of approx. 18-20°C and avoid draughts (keep windows closed, heat moderately in winter).

6. remove protruding edges

Trim any protruding edges with a cutter knife after drying.

Important note:

We endeavour to send only flawless goods through targeted quality control. Slight differences in colour are due to technical reasons. Lay out the motif before gluing and check for colour differences. If, despite everything, there is reason for complaint, please bring it to us before gluing, as we cannot be held liable for gluing costs.